



T11S Series Interlocking Brick Clamp



Model No.	Capacity @ 24" LC	Range Inside Forks	Fork Length	Mtg	Weight	ET	HCG	VCG	A	B	C
T11-50-42SM	5000	9 - 58	42	II / III	1007	7.0	6.1	11.0	43	25.1	5
T11-50-48SM	5000	9 - 58	48	II / III	1032	7.0	7.0	10.7	43	25.1	5
T11-50-54SM	5000	9 - 58	54	II / III	1058	7.0	8.0	10.5	43	25.1	5
T11-80-42SM	6500	9 - 58	42	III	1591	7.9	6.3	14.1	44	31.0	6
T11-80-48SM	6500	9 - 58	48	III	1621	7.9	7.0	13.8	44	31.0	6
T11-80-54SM	6500	9 - 58	54	III	1652	7.9	7.8	13.6	44	31.0	6
T11-100-42SM	8000	9 - 58	42	IV	2607	10.3	7.1	15.8	44	35.8	8
T11-100-48SM	8000	9 - 58	48	IV	2661	10.3	7.9	15.5	44	35.8	8
T11-100-54SM	8000	9 - 58	54	IV	2716	10.3	8.7	15.2	44	35.8	8

Specifications shown above are calculated without slip-on pads
Hydraulic Requirements: Double function auxiliary kit



Clamp shown without slip-on pads

Forks open and close equally and sideshift left or right

Things we need to know...

- ✓ Weight of Load
- ✓ Max. Width of Load
- ✓ Height of Load
- ✓ Length of Load
- ✓ Length of Fork
- ✓ Min. Width of Load
- ✓ Forklift Capacity